



► **TYRE: RT-4A**

**HAULAGE SERVICE
150 LEVEL**

INNOVATION:

- Excellent performance in rock, clay and wet conditions
- Superb forward and lateral traction

► **TYRE: RT-4A**





THE RT-4A IS SPECIFICALLY DESIGNED TO GIVE SUPERIOR PERFORMANCE IN OPERATIONS WHERE TRACTION IS NEEDED.

The RT-4A is a 150 level non-directional tyre for high speed haulage.

► **ENGINEERING DATA**

| Dimension | | Design Rim Width | Inflated Dimensions | | Loaded Tyre | | Rolling Circumference mm |
|------------|----------|------------------|---------------------|---------------------|----------------------------|-------------------------|--------------------------|
| | | | Overall Width mm | Overall Diameter mm | Loaded Section & Growth mm | Static Loaded Radius mm | |
| 18.00R33 | Tubeless | 13.00/2.5 | 512 | 1874 | 575 | 861 | 5652 |
| • 24.00R35 | Tubeless | 17.00/3.5 | 683 | 2185 | 757 | 1003 | 6590 |
| • 27.00R49 | Tubeless | 19.50/4.0 | 752 | 2700 | 848 | 1237 | 8143 |

• RT-4A+

► **LOADS AND INFLATION**

FOR TRANSPORT SERVICE AT 50KM/H MAXIMUM SPEED

| Dimension | SM | Load Speed Index | Loads per Tyre in Kilos and Inflation Bar | | | | | | | | | | |
|------------|----|------------------|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|---------|
| | | | 4.00 | 4.50 | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
| 18.00R33 | ** | 191B | 7100 | 7750 | 8500 | 8750 | 9000 | 9250 | 9750 | 10000 | 10300 | 10600 | 10900** |
| • 24.00R35 | ** | 209B | 12150 | 13200 | 14000 | 14500 | 15500 | 16000 | 16500 | 17000 | 17500 | 18000 | 18500** |
| • 27.00R49 | ** | - | 17500 | 19500 | 20600 | 21800 | 22400 | 23000 | 23600 | 25000 | 25750 | 26500 | 27250** |

• RT-4A+